

# FARM I<sup>®</sup>

## FOREST



Reliable skidding winch engineering with over 45-years experience



290



351P



501

- The automatic over-running brake device guarantees a very smooth pull-out of the cable and prevents run on
- A high pivoted cable entry guarantees optimum spooling into the cable drum
- Decades experience in all weather conditions

The FARMI 290 (with 6,400 lbs pull) and 351P (with 7,700 lbs pull) are ideal cable winches for small tractors from 15 HP and up. The standard models include an upper cable pulley and rugged butt plate with notched beam. The 351P comes with a lower guide pulley. The FARMI 501 winch (with 11,000 lbs pull for tractors from 35 HP and up) is manufactured with an integrated butt plate and a vertically adjustable lower cable pulley: a rugged and stable winch.



Power shaft in the center line of the winch

## FARMI Skidding winches: Technical information

	290	351P	501
Pulling force, max. lbs	6,400	7,700	11,000
Cable capacity	ø 5/16", 262' ø 3/8", 180'	ø 5/16", 295' ø 3/8", 196'	ø 5/16", 327' ø 3/8", 262' ø 1/2", 196'
Feed-in speed	350 rpm, feet/s 540 rpm, feet/s	.6 - 3.2	1-3 1.6 - 4.6
Mechanical plate coupling	yes	yes	yes
Required power, min. hp	from 15	from 15	from 35
Automatic drum brake	yes	yes	yes
Weight without the cable, lbs	330	374	551
Three-point mounting	Cat. I	Cat. I and Cat. II	Cat. I and Cat. II
Dozer blade and notched beam	yes	yes	yes
Protective screen	standard	standard	standard
Lower guide pulley	no	yes	yes
Holders for long chains	yes	yes	yes
Tool box	no	no	yes

We reserve the right to make changes.

29-501US /09/2012



Farmi Forest Corporation  
 Ahmolantie 6  
 FI-74510 Iisalmi  
 FINLAND  
 Tel. +358 17 832 41  
 Fax +358 17 382 4372  
 info@farmiforest.fi